



## Declaration of Performance according to EU BauPVO 305/2011

<b>1 DoP Reference number</b>	ST/G1/5028		
<b>2 Product description</b>	Separator for light liquids Oleopator-C-Bypass-HPC-LLT		
<b>3 Product specification: (Numbers or Specification of product)</b>	Oleopator-C-Bypass-HPC-LLT NS (x) / NS (y) / ST (z) (see following page)		
<b>4 Intended use</b>	Light liquid removal from wastewater to protect drainage systems and surface water		
<b>5 Manufacturer</b>	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
<b>6 Authorised representative</b>	Irrelevant		
<b>7 Assessment and verification of constancy of performance</b>	System 3 and System 4		
<b>8 Relevant harmonised standard</b>	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
<b>9 First year of CE marking</b>	2023		
<b>10 Notified body</b>	Irrelevant		
<b>11 Type test report reference number</b>	Irrelevant		
<b>12 Essential characteristics</b>	<b>Main features</b>	<b>DIN EN 858-1</b>	<b>Performance</b>
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
Durability	6.2	pass	
<b>13 Specific technical documentation (article 37/38)</b>	Installation manual		
<b>14 Other information</b>	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12.  
The manufacturer only is responsible for the creation of this declaration of performance according to No. 5.  
Signed for and on behalf of the manufacturer.

Bürstadt, 21.07.2023

Dennis Papadopoulos  
Managing Director





## Declaration of Performance according to EU BauPVO 305/2011

### Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt  23
DIN EN 858-1:2005  separator systems for light liquids Oleopator-C-Bypass-HPC-LLT class I with integrated sludge trap  Material: concrete Installation parts: PE-HD

### Overview of the CE marked separator systems for light liquids Type Oleopator-C-Bypass-HPC-LLT

NS (x)	NS (y)	ST (z)	Oil storage capacity (l)	Ø D (mm)
8	80	1600	378	1500
10	100	1000	330	1500
10	100	2000	330	1500
15	150	1500	805	2200
15	150	3000	805	2200
20	200	2000	1086	2200
20	200	4000	1086	2200
30	300	3000	1253	2200

